

Pre-varnish for interior woodwork



Ensures a long lasting and quality finish to wooden flooring.

Purpose

Liberon Pre-varnish gives a long lasting and quality finish to wood and parquet flooring. Recommend for use on sanded floors it reduces the darkening of wood and helps prevent tannins rising to keep the original beauty of the wood when it is varnished. Suitable for use with Liberon High Resistance Floor Varnish, Liberon Pre-varnish reinforces the durability of the varnish and aids application. Pre-varnish is recommended for use on Oak, Pine and most woods.

Performance

- Aids the adhesion and hardening of floor varnish
- Helps to reduce the darkening of wood when applying a varnish
- Provides a water resistant coating
- Ideal for old oak and pine
- Recommended for use with Liberon High Resistance Floor Varnish
- Endorsed by the Guild of Master Craftsmen
- Usage : Interior



How to Use

Preparation

Ensure that the surface is clean and dry. De-wax, sand and remove dust as required.

Application

Shake / stir well before use. The product has a milky appearance which disappears after application. Apply one coat of Pre-varnish evenly using a brush or roller. Allow to dry for a minimum of 1 hour, lightly sanding the surface with a fine sand paper before applying a finish of varnish.

Important

Always test product on a spare surface or inconspicuous area for colour change, compatibility and end result.

Liberon Advice

After sanding and cleaning the floor, wipe over with a damp cloth to remove any remaining sawdust. Ideal application conditions are between 12 and 25 C.

Precautions

For use with solvent varnish only. Do not use with oil finishes.

Coverage: 1L = 8-10m²

Pack Size: 750ml and 2.5L

Drying Time: Minimum 1 hour