

Hardwearing Varnish



Offers maximum protection against heat, water and alcohol.

Purpose

Liberon Hardwearing Varnish is ideal for use on surfaces that require maximum protection from water, heat and alcohol such as table tops, bar tops and bathroom furniture.

Performance

- High quality polyurethane varnish
- Gives a soft matt to satin sheen
- Maximum protection against heat, water and alcohol
- Highly scratch resistant
- Ideal for use on table tops, bar tops, kitchen worktops and in the bathroom
- Usage : Interior



How to Use

Preparation

Ensure the surface is clean, dry and free from dust or previous finishes. If you want to colour the wood you can apply Liberon Spirit Wood Dye or Liberon Palette Wood Dye to the timber before varnishing. Liberon Dyes are available in a range of wood shades.

Application

For best results dilute the first coat of varnish with 10-15% white spirit. Apply a thin coat of varnish with a fine brush, working with the grain. Allow to dry for a minimum of 8 hours before applying a second coat of varnish, lightly sanding between coats. Three or more coats may be required in areas of heavy use.

Important

Always test product on a spare surface or inconspicuous area for colour, compatibility and end results. A wet surface will be an indication of the final colour.

Precautions

- To ensure a hardwearing surface allow the final coat of varnish to dry for a minimum of 24 hours before use.
- Allow all wood dyes to dry thoroughly before applying the varnish. Care must be taken on the application of the first coat of Hardwearing Varnish when being used over Liberon Spirit Wood Dye. Keep brush strokes to a minimum as over brushing may lift out the colour.

Colours: Clear satin

Coverage: 1L = 8-12m²

Pack Size: 750ml, 2.5L

Drying Time: Minimum 8 hours