

High Protection Woodstain



Protects, treats and provides a durable finish to new and old interior and exterior wood.

Purpose

Liberon High Protection Woodstain is a triple action product that protects, treats and provides a durable finish to new and old interior and exterior wood. Guaranteed for 4 years it is ideal for use on interior and exterior timber such as gates, fences, window frames, panelling and beams.

Performance

- Highly resistant to UV rays and bad weather conditions
- Non drip formula is ideal for vertical surfaces
- Touch dry in 30 minutes
- Up to 4 years protection



How to Use

Preparation

Ensure the surface is clean and dry.

Bare wood: brush and remove all traces of dust. For greater protection timber may be treated with an exterior wood preserver before applying High Protection Woodstain.

Previously stained wood: brush the timber to remove any flaking pieces, sand to a smooth surface and remove all dust.

Varnished or painted wood: strip the timber with a general wood stripper. Neutralise in accordance with wood stripper manufacturers instructions, then rinse with water and allow to dry for 24 hours. Sand and remove all dust.

Oily wood: degrease before applying High Protection Woodstain.

Application

Stir well with a stirring stick before use.

Apply a minimum of 2 coats of High Protection Woodstain with a brush, spray (10% dilution with water) or a roller (specially designed for woodstains).

Allow 3 hours to dry between coats.

On new or heavily exposed timber we recommend applying a third coat when using a light coloured stain.

Ideal conditions for application are between 12 and 25C on wood that is not too hot in order to avoid drying marks.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Colours: Satin

Coverage: 1L = 12m² depending on condition of wood

Pack Size: 750ml and 2.5L

Drying Time: 30min touch - 3h between coats - 12h final