

# Two-part Wood Filler



***A hardwearing wood substitute used to reconstitute missing sections of wood.***

## Purpose

Liberon Two Part Wood Filler is made from a mix of wood flour and polyester resin to produce a hardwearing wood substitute. Used to reconstitute missing sections of wood in floors, tables and window frames etc., Liberon Two Part Wood Filler is fast curing and shrink resistant. It can be sanded, nailed and dyed once hardened. The high strength formula is resistant to water and is compatible with most finishing products. Ideal for use prior to painting.

## Performance

- Epoxy strength can replace complete sections of wood
- Fast curing
- Shrink and crack resistant
- Suitable for interior and exterior use
- Endorsed by the Guild of Master Craftsmen
- Usage: Interior and exterior



## How to Use

### Preparation

Ensure the area to be repaired is clean, dry and free from dust.

### Application

Mix a pea size amount of hardener with a soup spoonful of wood filler in the plastic lid. Always work with small quantities as the product hardens very quickly. Immediately place the filler onto the area requiring filling using a Liberon Plastic Scraper or suitable filling knife. Working time of 5- to 10 minutes. The wood filler can be sanded once it has hardened (approximately 30 minutes). Small holes may be filled in one operation. Bigger areas may be built up in layers.

### Important

Two Part Wood Filler will accept dyes/stains differently to surrounding wood.

Colours: Neutral

Coverage: As required

Pack Size: 200g

Drying Time: 30 mins